C	Aterial Composit Copyright 2005. IPC, International and Pan-An	Bannockb	urn, Illinois. A	ll rights reserved nations.	under both	This docum level parts,	ent is a declarat	ion of the successed	ubstances v s all lower	within the manufacture level materials for v	urer listed	item. Note: nanufacture	if the item is an as er has engineering	sembly with low responsibility.	
					Form Type Distribute	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					rials and M	als and Mfg Information			
Supplier Information	on														
Company name*			Company unique ID				Unique ID Authority				Respon	Response Date*			
onsemi											2023-06	2023-06-08			
Contact Name			Title - Contact				Phone - Contact*				Email -	Email - Contact*			
Product-Env-Stewards			Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
Authorized Representative*			Title - Representative				Phone - Representative*				Email -	Email - Representative*			
Product-Env-Stewards			Product Enviro Compliance				NA				Produe	Product-Env-Stewards@onsemi.com			
Requester Ite	em Number			umber Mfr Item Name			Effective Date	Version	Ν	Manufacturing Site		Weight*	UOM	Unit Type	
		NCP5217AMNTXG SYNC ST		SYNC STEP DC	NC STEP DOWN CONTROLLER		2023-06-08		N	MY1		28.57	mg	Each	
Anufacturing Pro	occess Information	1							I						
Terminal Plati	Terminal Plating / Grid Array Material Termin		erminal Base A	nal Base Alloy J-STD-020 MSI		L Rating	Peak Proc	ak Process Body Temperatu		are Max Time at Peak Tempera		ture Num	ber of Reflow Cyc	eles	
Matte Tin (Sn) - annealed		CU Alloy 1		1		260		C 30		seconds 3					
omments															
vel 1 - maximum time	at peak temperature d	luring sol	dering is 10-3	0 seconds											
or more information re	egarding material com	position	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Disobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	Supplier Acceptance	* Accepted								
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all						
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	stislav Drska	Le									

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.16	mg	Supplier	Silicon (Si)	7440-21-3		0.16	mg
Die Attach	0.41	mg	Supplier	Silver (Ag)	7440-22-4		0.3075	mg
			Supplier	Epoxy resins	129915-35-1		0.1025	mg
Lead Frame	8.91	mg	Supplier	Silver (Ag)	7440-22-4		0.6593	mg
			Supplier	Copper (Cu)	7440-50-8		8.2507	mg
Mold Compound-Black	16.46	mg		Epoxy resin	proprietary data		1.1522	mg
			Supplier	Phenolic Resin	Proprietary Data		1.1522	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		2.469	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0823	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		11.6043	mg
Plating	0.6	mg	Supplier	Tin (Sn)	7440-31-5		0.6	mg
Wire Bond - Au	2.03	mg	Supplier	Gold (Au)	7440-57-5		2.03	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3