ΡΟΝ Νι	umber:	201606060	001			PCN Da	ate:	06/09/20	)16
Title:	Datasheet fo								
Custon	ner Contact:	PCN Manager	-		De	pt:	Oua	lity Service	es
Change	e Type:		_				L C	,	
	sembly Site		Design			Wafer	<sup>-</sup> Bum	p Site	
	sembly Process		Data Shee	t				p Material	
Ass	sembly Materia	ls	Part numb	er change		Wafer	- Bum	p Process	
	chanical Specif		Test Site			Wafer			
Pao	cking/Shipping,	/Labeling	Test Proce	SS				Materials	
						Wafer	r Fab I	Process	
			Notificatio	n Details					
	otion of Chan			·		L:C			
			announcing an ed as seen in the						
ine più				e change revisi		SLOTY D	.000		
	-NOVEMBER 2008-REV						IE IN	XAS STRUMENTS www.ti.com	<u>1</u>
Changes	from Original (Nov	ember 2008) to I	Revision A					Page	-
-									
<ul> <li>Chang</li> </ul>	jed TPS2115A to TP	S2155A-Q1 throu	ughout document					1	1
<ul> <li>Added</li> </ul>			gs table, Feature Des					nd	
Applica			anical, Packaging, an	endations section, La d Orderable Informa					1
Applica Docun	nentation Support se	ection, and Mecha		d Orderable Informa	tion se	ction		1	
Applica Docun • Chang • Moved	nentation Support se ed Continuous outp I Figure 1 to Switchi	ection, and Mecha ut current from 1. ng Characteristics	anical, Packaging, an 5mA to 1.5A in Abso s section	d Orderable Informa lute Maximum Ratino	tion se gs tabl	ction e		1 	3 5
Applica Docum Chang Moved Moved	nentation Support se ged Continuous outp d Figure 1 to Switchin d test circuits from T	ection, and Mecha ut current from 1. ng Characteristics vpical Characteris	anical, Packaging, an 5mA to 1.5A in Abso s section stics to Parameter Me	d Orderable Informa lute Maximum Rating easurement Informat	tion se gs tabl ion sec	ction e ction			3 5 7
<ul> <li>Applica Docum</li> <li>Chang</li> <li>Moved</li> <li>Moved</li> </ul>	nentation Support se ged Continuous outp d Figure 1 to Switchin d test circuits from T	ection, and Mecha ut current from 1. ng Characteristics vpical Characteris	anical, Packaging, an 5mA to 1.5A in Abso s section	d Orderable Informa lute Maximum Rating easurement Informat	tion se gs tabl ion sec	ction e ction			3 5 7
<ul> <li>Applica Docum</li> <li>Chang</li> <li>Moved</li> <li>Moved</li> </ul>	nentation Support se ged Continuous outp d Figure 1 to Switchin d test circuits from T	ection, and Mecha ut current from 1. ng Characteristics vpical Characteris	anical, Packaging, an 5mA to 1.5A in Abso s section stics to Parameter Me	d Orderable Informa lute Maximum Rating easurement Informat	tion se gs tabl ion sec	ction e ction			3 5 7
Applica Docum Chang Moved Moved Chang	nentation Support se Jed Continuous outp d Figure 1 to Switching t test circuits from Ty Jed info in D0 column	ection, and Mecha ut current from 1. ng Characteristics vpical Characteris	anical, Packaging, an 5mA to 1.5A in Abso s section stics to Parameter Me	d Orderable Informa lute Maximum Rating easurement Informati table to Device Fur	tion se gs tabl ion sec	ction e ction	section .		3 5 7
Applica Docum Chang Moved Chang Device	nentation Support se ged Continuous outp d Figure 1 to Switchin d test circuits from Ty ged info in D0 column e Family	ection, and Mecha ut current from 1. ng Characteristics vpical Characteris	anical, Packaging, an 5mA to 1.5A in Abso s section stics to Parameter Me	d Orderable Informa lute Maximum Rating easurement Informat table to Device Fur Change Fro	tion se gs tabl ion sec	ction e ction	section . Chan		3 5 7
Applica Docum Chang Moved Moved Chang Device TPS21	nentation Support se jed Continuous outp d Figure 1 to Switchin d test circuits from 7) jed info in D0 column e Family 15A-Q1	ection, and Mecha ut current from 1. ng Characteristics ypical Characteris n with info from D	anical, Packaging, an 5mA to 1.5A in Absol s section stics to Parameter Me 01 column and moved	d Orderable Informa lute Maximum Rating easurement Informati table to Device Fur Change Fro SBVS124	tion se gs tabl ion sec	ction e ction	section . Chan		3 5 7
Applica Docum Chang Moved Chang Device TPS21 These c	nentation Support se jed Continuous outp d Figure 1 to Switchin d test circuits from 7) jed info in D0 column e Family 15A-Q1	ection, and Mecha ut current from 1. ng Characteristics pical Characteris n with info from D e reviewed at	anical, Packaging, an 5mA to 1.5A in Absol s section stics to Parameter Me 1 column and moved to column and moved the datasheet	d Orderable Informa lute Maximum Rating easurement Informati table to Device Fur Change Fro SBVS124	tion se gs tabl ion sec	ction e ction	section . Chan		3 5 7
Applica Docum Chang Moved Chang Device TPS21 These c http://w	nentation Support se jed Continuous outp d Figure 1 to Switchi d test circuits from Ty jed info in D0 column E Family 15A-Q1 hanges may be	ection, and Mecha ut current from 1. ng Characteristics pical Characteris n with info from D e reviewed at	anical, Packaging, an 5mA to 1.5A in Absol s section stics to Parameter Me 1 column and moved to column and moved the datasheet	d Orderable Informa lute Maximum Rating easurement Informati table to Device Fur Change Fro SBVS124	tion se gs tabl ion sec	ction e ction	section . Chan		3 5 7
Applica Docum Chang Moved Chang Device TPS21 These c http://v	nentation Support se Jed Continuous outp 1 Figure 1 to Switchin 1 test circuits from Ty Jed info in D0 column 2 Family 15A-Q1 hanges may be www.ti.com/pro	ection, and Mecha ut current from 1. <i>ng Characteristics</i> <i>pical Characteris</i> n with info from D e reviewed at <u>oduct/tps211</u>	anical, Packaging, an 5mA to 1.5A in Absol s section stics to Parameter Me 1 column and moved to column and moved to the datasheet 5a-q1	d Orderable Informa lute Maximum Rating easurement Informati table to Device Fur Change Fro SBVS124	tion se gs tabl ion sec	ction e ction	section . Chan		3 5 7
Applica Docum Chang Moved Chang Device TPS21 These c http://w Reason To more	nentation Support se jed Continuous outp d Figure 1 to Switchin d test circuits from Ty jed info in D0 column e Family 15A-Q1 changes may be www.ti.com/pro- n for Change: e accurately ref	ection, and Mecha ut current from 1. Ing Characteristics pical Characteris n with info from D e reviewed at oduct/tps211	anical, Packaging, an 5mA to 1.5A in Absol s section stics to Parameter Me 1 column and moved to column and moved to the datasheet 5a-q1	d Orderable Informa lute Maximum Rating easurement Informati table to Device Fur Change Fro SBVS124 links provided.	tion see gs tabl ion see actiona	ction e ction / Modes s	Chan SBV	ige To: <b>S124A</b>	3 5 7 2 -
Applica Docum Chang Moved Moved Chang Device TPS21 These c http://v Reason To more Anticip No antic	nentation Support se jed Continuous outp d Figure 1 to Switchin d test circuits from 7) jed info in D0 column e Family 15A-Q1 changes may be www.ti.com/pro- n for Change: e accurately ref pated impact of	ection, and Mecha ut current from 1. Ing Characteristics pical Characteris n with info from D e reviewed at oduct/tps211.	anical, Packaging, an 5mA to 1.5A in Absol s section stics to Parameter Me of column and moved to the datasheet 5a-q1 haracteristics.	d Orderable Informa lute Maximum Rating easurement Information table to Device Fur Change Fro SBVS124 links provided.	tion see gs tabl ion see actiona om : bility	ction e ction / <i>Modes</i> s	Chan SBVS	ige To: 5124A	e):
Applica Docum Chang Moved Chang Device TPS21 These C http://w Reason To more Anticip No antic to the a	e Family 15A-Q1 hanges may be www.ti.com/pro	ection, and Mecha ut current from 1. ng Characteristics pical Characteris n with info from D e reviewed at oduct/tps211	anical, Packaging, an 5mA to 1.5A in Absol s section stics to Parameter Me of column and moved to column and moved to the datasheet 5a-q1 haracteristics. a, Function, Qu	d Orderable Informa lute Maximum Rating easurement Information table to Device Fur Change Fro SBVS124 links provided.	tion see gs tabl ion see actiona om : bility	ction e ction / <i>Modes</i> s	Chan SBVS	ige To: 5124A	e):
Applica Docum Chang Moved Moved Chang Device TPS21 These c http://v Reason To more Anticip No antic to the a Change	e Family 15A-Q1 hanges may be www.ti.com/pro	ection, and Mecha ut current from 1. ng Characteristics pical Characteris n with info from D e reviewed at oduct/tps211	anical, Packaging, an 5mA to 1.5A in Absol s section stics to Parameter Me 1 column and moved to the datasheet 5a-q1 haracteristics. <b>5, Function, Qu</b> ecification chang	d Orderable Informa lute Maximum Rating easurement Information table to Device Fur Change Fro SBVS124 links provided.	tion see gs tabl ion see actiona om : bility	ction e ction / <i>Modes</i> s	Chan SBVS	ige To: 5124A	e):
Applica Docum Chang Moved Moved Chang Device TPS21 These c http://v Reason To more Anticip No antic to the a Change None.	e Family 15A-Q1 hanges may be www.ti.com/pro	ection, and Mecha ut current from 1. ng Characteristics pical Characteris n with info from D e reviewed at oduct/tps211	anical, Packaging, an 5mA to 1.5A in Absol s section stics to Parameter Me 1 column and moved to the datasheet 5a-q1 haracteristics. <b>5, Function, Qu</b> ecification chang	d Orderable Informa lute Maximum Rating easurement Information table to Device Fur Change Fro SBVS124 links provided.	tion see gs tabl ion see actiona om : bility	ction e ction / <i>Modes</i> s	Chan SBVS	ige To: 5124A	e):
Applica Docum Chang Moved Moved Chang Device TPS21 These c http://w Reason To more Anticip No antic to the a Change None. Produce	e Family 15A-Q1 hanges may be www.ti.com/pro	ection, and Mecha ut current from 1. ng Characteristics pical Characteris n with info from D e reviewed at oduct/tps211	anical, Packaging, an 5mA to 1.5A in Absol s section stics to Parameter Me 1 column and moved to the datasheet 5a-q1 haracteristics. <b>5, Function, Qu</b> ecification chang	d Orderable Informa lute Maximum Rating easurement Information table to Device Fur Change Fro SBVS124 links provided.	tion see gs tabl ion see actiona om : bility	ction e ction / <i>Modes</i> s	Chan SBVS	ige To: 5124A	e):
Applica Docum Chang Moved Chang Device TPS21 These c http://w Reason To more Anticip No antic to the a Change None. Produc TPS211 For que	e Family 15A-Q1 hanges may be www.ti.com/pro for Change: accurately ref bated impact of cipated impact. actual device. bated for Change: bated impact of cipated impact. bated impact. bated impact. bated impact of cipated impact. bated impact. b	ection, and Mecha ut current from 1. Ing Characteristics upical Characteristics in with info from D e reviewed at oduct/tps211. Flect device c on Fit, Form This is a spe identification g this notice	anical, Packaging, an 5mA to 1.5A in Absol s section stics to Parameter Me 1 column and moved to column and moved to column and moved to column and moved to column and moved the datasheet 5a-q1 haracteristics. <b>5</b> , <b>Function, Qu</b> ecification change <b>on resulting fr</b> , e-mails can be	d Orderable Informa lute Maximum Rating easurement Information table to Device Fur Change Fro SBVS124 links provided.	tion see gs tabl ion see octiona om: bility ent o	ction e / Modes s / Modes s	Chan SBVS	ige To: 5124A / negative re no chane	e): ges
Applic Docum Chang Moved Moved Chang Device TPS21 These c http://v Reason To more Anticip No antic to the a Change None. Produc TPS211 For que or your Locatic	e Family 15A-Q1 hanges may be www.ti.com/pro a for Change: a accurately ref bated impact of cipated impact. actual device. bated impact cipated impact. actual device. bated impact cipated impact. bated impact of cipated impact of cipated impact. bated impact of cipated impact of cipated impact of cipated impact of cipated impact of cipated impact. bated impact of cipated impact. bated impact of cipated impact. bated impact of cipated impact. bated impact of cipated impact of cipated impact. bated impact of cipated impact of cipated impact. bated impact of cipated impact of ci	ection, and Mecha ut current from 1. Ing Characteristics upical Characteristics in with info from D e reviewed at oduct/tps211. Flect device c on Fit, Form This is a spe identification g this notice	anical, Packaging, an 5mA to 1.5A in Absol s section stics to Parameter Me 1 column and moved the datasheet 5a-q1 haracteristics. <b>a, Function, Qu</b> ecification chang <b>on resulting fr</b> , e-mails can be ative. <b>E-</b>	d Orderable Informa lute Maximum Rating easurement Information table to Device Fur Change Fro SBVS124 links provided.	tion see gs tabl ion see actiona om: billity ent o	ction e ition / Modes s / Modes s / Modes s	Chan SBVS	ige To: 5124A / negative re no chane	e): ges
Applica Docum Chang Moved Moved Chang Device TPS21 These c http://v Reason To more Anticip No antic to the a Change None. Produc TPS211 For que or your	e Family 15A-Q1 hanges may be www.ti.com/pro a for Change: a accurately ref bated impact of cipated impact. actual device. bated impact cipated impact. actual device. bated impact cipated impact. bated impact of cipated impact of cipated impact. bated impact of cipated impact of cipated impact of cipated impact of cipated impact of cipated impact. bated impact of cipated impact. bated impact of cipated impact. bated impact of cipated impact. bated impact of cipated impact of cipated impact. bated impact of cipated impact of cipated impact. bated impact of cipated impact of ci	ection, and Mecha ut current from 1. Ing Characteristics upical Characteristics in with info from D e reviewed at oduct/tps211. Flect device c on Fit, Form This is a spe identification g this notice	anical, Packaging, an 5mA to 1.5A in Absol s section stics to Parameter Me 1 column and moved the datasheet 5a-q1 haracteristics. <b>5. Function, Qu</b> ecification chang <b>on resulting fr</b> , e-mails can be ative. <b>E-</b> PC	d Orderable Informa lute Maximum Rating easurement Information table to Device Fur SBVS124 links provided.	tion see gs tabl ion see actiona om: bility ent o giona	ction e / Modes s / Modes s / I conta al conta	Chan SBVS	ige To: 5124A / negative re no chane	e): ges
Applica Docum Chang Moved Moved Chang Device TPS21 These c http://w Reason To more Anticip No antio to the a Change None. Produc TPS211 For que or your Locatio USA Europe	e Family 15A-Q1 hanges may be www.ti.com/pro for Change: accurately ref accurately ref bated impact of cipated impact. actual device. bated impact cipated impact	ection, and Mecha ut current from 1. Ing Characteristics upical Characteristics in with info from D e reviewed at oduct/tps211. Flect device c on Fit, Form This is a spe identification g this notice	anical, Packaging, an 5mA to 1.5A in Absol s section stics to Parameter Me 1 column and moved haracteristics. <b>5a-q1</b> haracteristics. <b>5, Function, Qu</b> ecification chang <b>on resulting fr</b> , e-mails can be ative. <b>E-</b> <u>PC</u> PC	d Orderable Informa lute Maximum Rating easurement Information table to Device Fur Change Fro SBVS124 links provided.	tion see gs tabl ion see actiona om: bility ent o giona <u>st@list.t</u>	ction e / Modes s / Modes s / I Modes s	Chan SBVS	ige To: 5124A / negative re no chane	e): ges
Applica Docum Chang Moved Moved Chang Device TPS21 These c http://v Reason To more Anticip No antic to the a Change None. Produc TPS211 For que or your Locatio USA	e Family 15A-Q1 hanges may be www.ti.com/pro for Change: accurately ref accurately ref bated impact of cipated impact. actual device. bated impact cipated impact	ection, and Mecha ut current from 1. Ing Characteristics upical Characteristics in with info from D e reviewed at oduct/tps211. Flect device c on Fit, Form This is a spe identification g this notice	anical, Packaging, an 5mA to 1.5A in Absol s section stics to Parameter Me 1 column and moved to column and moved to column and moved to column and moved to column and moved the datasheet 5a-q1 haracteristics. <b>5.</b> <b>5.</b> <b>5.</b> <b>5.</b> <b>5.</b> <b>5.</b> <b>5.</b> <b>6.</b> <b>7.</b> <b>6.</b> <b>7.</b> <b>7.</b> <b>7.</b> <b>7.</b> <b>7.</b> <b>7.</b> <b>7.</b> <b>7</b>	d Orderable Informa lute Maximum Rating easurement Information table to Device Fur SBVS124 links provided.	tion see gs tabl ion see octiona om: om: om: om: om: om: om: om: om: om:	ction e / Modes s / Modes s / Inly. The al conta t.ti.com om	Chan SBVS	ige To: 5124A / negative re no chane	e): ges