


**Specification Status: Released**

**Maximum Electrical Rating**


**Voltage: 6V<sub>DC</sub>**  
**Short Circuit Current: 100A**



**Notes:**

1. All terminations are tin/lead plated.
2. Devices can be wave soldered.
3. Drawing not to scale

**Marking:**



**TABLE I. DIMENSIONS:**

	A		B		C		D	E	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MIN	MAX
mm:	4.37	4.73	3.07	3.41	0.51	1.22	0.30	0.25	--
in:	(0.172)	(0.186)	(0.121)	(0.134)	(0.020)	(0.048)	(0.012)	(0.010)	--

**TABLE II. PERFORMANCE RATINGS:**

IHOLD ** RATED CURRENT	CURRENT TRIP LIMITS**						TIME TO TRIP **	RESISTANCE VALUES		TRIPPED- STATE POWER DISSIPATION**
	AMPERES AT 20°C HOLD	AMPERES AT -40°C HOLD	AMPERES AT 20°C TRIP	AMPERES AT 60°C HOLD	AMPERES AT 60°C TRIP	AMPERES AT 60°C TRIP		SECONDS AT 20°C, 8A MAX	OHMS AT 20°C MIN	
2.00	2.60	6.00	2.00	4.00	1.50	3.00	5	0.020	0.070	1.0

\* Maximum resistance is measured 1 hour after reflow

\*\*Values Specified were determined using PCB's with 0.030"X1.5 ounce copper traces.

Reference Documents: PS300, E. N. SMD1.0x.  
 Precedence: This specification takes precedence over documents referenced herein.  
 Effectivity: Reference documents shall be the issue in effect on the date of invitation for bid.  
 CAUTION: Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.