| PCN Number: | 2014111700 | nn | | PCN Date: | 11/18/2014 |
|---|--|---|-----------|--|-----------------|
| | asheet change | | • | CIT Date. | 11/10/2014 |
| Customer Contact: | PCN Manager | Phone: +1(214) 480-603 | 7 | Dept: Qu | ality Services |
| Change Type: | 1 CIV Mariager | Filone: +1(214) 480-003 | / | Dept. Qu | iality Services |
| Assembly Site | | Design | | Wafer Bun | on Site |
| Assembly Process | | Data Sheet | H | | |
| Assembly Materials | | Part number change | \forall | Wafer Bump Material Wafer Bump Process | |
| Mechanical Specification | | Test Site | H | Wafer Fab | |
| Packing/Shipping/Labeling | | Test Process | \exists | Wafer Fab Materials | |
| T deking/ Shipping/ | Labeling | Test riocess | Ħ | Wafer Fab | |
| PCN Details | | | | | |
| Description of Chang | ge: | | | | |
| | | nnouncing an information only | no | tification. | |
| | | - | | | |
| | (s) is being up | odated to change the ESD spe | an | d updated A | AFE Register |
| Description | | | | | |
| | | | | | |
| The following shange h | aiatam, provida | a further details | | | |
| The following change h | listory provide | es further details | | | |
| | | | | √ Ü Ţ | EXAS |
| AFE4490 | | | | ■ II | NSTRUMENTS |
| SBAS602H - DECEMBER 2012-REVI | ISED OCTOBER 2014 | | | | www.ti.com |
| | | | | | |
| Changes from Revision G (June 2014) to Revision H | | | | | Page |
| | | | | | |
| | · · · · · · · · · · · · · · · · · · · | s in Absolute Maximum Ratings table | | | |
| Changed V _(ESD) parameter | r specification value | | | | 8 |
| Changed V _(ESD) parameter | r specification value | s in Absolute Maximum Ratings table | | | 8 |
| Changed V _(ESD) parameter Updated AFE Register De | r specification value escription section to | es in Absolute Maximum Ratings table current standards: added legend and bit | | | 8 |
| Changed V _(ESD) parameter Updated AFE Register De The datasheet number | r specification value escription section to will be changi | es in Absolute Maximum Ratings table current standards: added legend and bit | settin | igs to each bit r | 8 |
| Changed V _(ESD) parameter Updated <i>AFE Register De</i> The datasheet number Device Family | r specification value escription section to will be changed | in Absolute Maximum Ratings table current standards: added legend and bit ing. ange From: | nan | gs to each bit re | 8 |
| Changed V _(ESD) parameter Updated AFE Register De The datasheet number | r specification value escription section to will be changed | in Absolute Maximum Ratings table current standards: added legend and bit ing. ange From: | nan | igs to each bit r | 8 |
| Changed V _(ESD) parameter Updated <i>AFE Register De</i> The datasheet number Device Family | r specification value escription section to will be changed | in Absolute Maximum Ratings table current standards: added legend and bit ing. ange From: | nan | gs to each bit re | 8 |
| Changed V _(ESD) parameter Updated AFE Register De The datasheet number Device Family AFE4490 | r specification value escription section to will be change Cha | in Absolute Maximum Ratings table current standards: added legend and bit ing. ange From: | nan | gs to each bit re | 8 |
| Changed V _(ESD) parameter Updated AFE Register De The datasheet number Device Family AFE4490 These changes may be | r specification value escription section to will be change Cha SBA | ing. ange From: CAS602G Che datasheet links provided. | nan | gs to each bit re | 8 |
| Changed V _(ESD) parameter Updated AFE Register De The datasheet number Device Family AFE4490 | r specification value escription section to will be change Cha SBA | ing. ange From: CAS602G Che datasheet links provided. | nan | gs to each bit re | 8 |
| Changed V _(ESD) parameter Updated AFE Register Description The datasheet number Device Family AFE4490 These changes may be http://www.ti.com/pro | r specification value escription section to will be change Cha SBA | ing. ange From: CAS602G Che datasheet links provided. | nan | gs to each bit re | 8 |
| Changed V _(ESD) parameter Updated AFE Register De The datasheet number Device Family AFE4490 These changes may be http://www.ti.com/pro | r specification value escription section to will be changed Changed SBA e reviewed at tooduct/afe44903 | ing. ange From: CAS602G Che datasheet links provided. | nan | gs to each bit re | 8 |
| Changed V _(ESD) parameter Updated AFE Register De The datasheet number Device Family AFE4490 These changes may be http://www.ti.com/pro Reason for Change: To more accurately ref | r specification value escription section to will be changed Changed SBA e reviewed at the enduct/afe44903 | ing. ange From: CAS602G Che datasheet links provided. Caggn=afe4490 Caracteristics. | nan | gs to each bit rege To: | |
| Changed V _(ESD) parameter Updated AFE Register De The datasheet number Device Family AFE4490 These changes may be http://www.ti.com/pro Reason for Change: To more accurately ref Anticipated impact of | r specification value escription section to will be changed to the change of the chan | ing. inge From: CAS602G Che datasheet links provided. Cagpn=afe4490 Caracteristics. Characteristics. Characteristics. | nan | gs to each bit rege To: | |
| Changed V _(ESD) parameter Updated AFE Register De The datasheet number Device Family AFE4490 These changes may be http://www.ti.com/pro Reason for Change: To more accurately ref Anticipated impact of Electrical specification | r specification value escription section to will be change Cha SBA e reviewed at to duct/afe44903 flect device cha performance of | ing. inge From: CAS602G Che datasheet links provided. Cagpn=afe4490 Characteristics. Function, Quality or Reliab Changes as indicated above. | nan | gs to each bit rege To: | |
| Changed V _(ESD) parameter Updated AFE Register De The datasheet number Device Family AFE4490 These changes may be http://www.ti.com/pro Reason for Change: To more accurately ref Anticipated impact of Electrical specification Changes to product | r specification value escription section to will be change Cha SBA e reviewed at to duct/afe44903 flect device cha performance of | ing. inge From: CAS602G Che datasheet links provided. Cagpn=afe4490 Caracteristics. Characteristics. Characteristics. | nan | gs to each bit rege To: | |
| Changed V _(ESD) parameter Updated AFE Register De The datasheet number Device Family AFE4490 These changes may be http://www.ti.com/pro Reason for Change: To more accurately ref Anticipated impact of Electrical specification Changes to product None. | r specification value escription section to will be change Cha SBA e reviewed at to duct/afe44903 flect device cha performance of | ing. inge From: CAS602G Che datasheet links provided. Cagpn=afe4490 Characteristics. Function, Quality or Reliab Changes as indicated above. | nan | gs to each bit rege To: | |
| Changed V _(ESD) parameter Updated AFE Register De The datasheet number Device Family AFE4490 These changes may be http://www.ti.com/pro Reason for Change: To more accurately ref Anticipated impact of Electrical specification Changes to product | r specification value escription section to will be change Cha SBA e reviewed at to duct/afe44903 flect device cha performance of | ing. inge From: CAS602G Che datasheet links provided. Cagpn=afe4490 Characteristics. Function, Quality or Reliab Changes as indicated above. | nan | gs to each bit rege To: | |

For questions regarding this notice, e-mails can be sent to the regional contacts shown below or your local Field Sales Representative.

| Location | E-Mail |
|--------------|--------------------------------|
| USA | PCNAmericasContact@list.ti.com |
| Europe | PCNEuropeContact@list.ti.com |
| Asia Pacific | PCNAsiaContact@list.ti.com |
| Japan | PCNJapanContact@list.ti.com |