ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES® INCLUSTRES®	IPC. Bannockl	ourn. Illinois. A	ll rights reserved untions.	under both	This docume level parts, t	ent is a declara the declaration	tion of the s encompass	substances es all lowe	within the er level ma	e manufacture terials for wh	er listed it hich the m	em. Note anufactu	e: if the ite arer has en	em is an asser ngineering res	nbly with low ponsibility.
				Form Type Distribute	*	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information				
Supplier Information															
Company name* Compa			ompany unique ID			Unique ID Authority					Response Date*				
consemi Title - Contact					Phone - Contact*						2023-06-08 Email - Contact*				
Product-Env-Stewards Product E			ict Enviro Compliance			NA				Product-Env-Stewards@onsemi.com					
Authorized Representative* Title - H			e - Representative			Phone - Representative*				Email - Representative*					
Product-Env-Stewards Produc			oduct Enviro Compliance			NA				Product-Env-Stewards@onsemi.com					
Requester Item Number	Mfr Iten	n Number	Mfr Item Name			Effective Dat	e Version	ı	Manufacturing Site		V	Veight*	U	ОМ	Unit Type
	NCV850	NCV8501DADJR2G ANA LDO LINEA		EAR REGULAT	OR	2023-06-08			PH1		7	2.0	m	ıg	Each
Manufacturing Proccess Informa	ntion							·			·		·		
Terminal Plating / Grid Array M	Terminal Plating / Grid Array Material Terminal Base Alloy			J-STD-020 MSI	) MSL Rating Peak Process Body Temperature Max Time					'ime at Peak '	eak Temperature Number of Reflow Cycles				
Matte Tin (Sn) - annealed CU Alloy				1		260		С	30		second	ls 3			
omments															
vel 1 - maximum time at peak temperat	ure during so	ldering is 10-3	0 seconds												
or more information regarding materia	composition	please refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless	otherwise noted).							
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	1.33	mg	Supplier	Silicon (Si)	7440-21-3		1.33	mg
Die Attach	2.4	mg		Epoxy resin	proprietary data		0.24	mg
			Supplier	Ethylene dimethacrylate	97-90-5		0.12	mg
			Supplier	Silver (Ag)	7440-22-4		1.92	mg
			Supplier	Formaldehyde Polymer	9003-36-5		0.12	mg
Lead Frame	37.61	mg	Supplier	Silver (Ag)	7440-22-4		0.7898	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0752	mg
			Supplier	Iron (Fe)	7439-89-6		0.9403	mg
			Supplier	Copper (Cu)	7440-50-8		35.8047	mg
Mold Compound-Black	28.58	mg		Epoxy resin	proprietary data		1.429	mg
			Supplier	Phenolic Resin	Proprietary Data		0.5716	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.7145	mg
			Supplier	Carbon Black (C)	1333-86-4		0.1429	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		25.722	mg
Plating	1.89	mg	Supplier	Tin (Sn)	7440-31-5		1.89	mg
Wire Bond - Au	0.19	mg	Supplier	Gold (Au)	7440-57-5		0.19	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).