ASSOCIATION CONNECTING	© Copyright 2005. IPC, international and Pan-Ar	Bannockb	urn, Illinois. A	Il rights reserved untions.	under both	This docum level parts, t	ent is a declarat he declaration e	ion of the su	ubstances s all lower	within the manufactu level materials for w	rer listed i which the n	tem. Note: nanufacture	if the item is an as or has engineering	ssembly with low responsibility.	
752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				e *	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information				
Supplier Inform	ation														
Company name*			Company unique ID				Unique ID Authority				Respon	Response Date*			
onsemi											2023-06	2023-06-08			
Contact Name			Title - Contact				Phone - Contact*				Email - Contact*				
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Authorized Representative*			Title - Representative			Phone - Representative*				Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance			NA				Produc	Product-Env-Stewards@onsemi.com				
Requester	Requester Item Number Mfr Iten		n Number Mfr Item Name				Effective Date Version Manufacturin		Ianufacturing Site		Weight*	UOM	Unit Type		
		MOC308	MOC3082SR2VM 6PW Z		PW ZC TRIAC T&R VDE		2023-06-08		LITEONFG		464.903		mg	Each	
Ianufacturing I	Proccess Information	n		-											
Terminal Plating / Grid Array Material Ter		erminal Base Alloy J-STD-020 MSL		L Rating	Peak Process Body Temperatu		emperatur	ure Max Time at Peak Temper		ture Num	ber of Reflow Cyc	cles			
Matte Tin (Sn) - annealed			U Alloy 1			260 C 30		30	seconds 3						
omments															
vel 1 - maximum ti	me at peak temperature o	luring sol	dering is 10-3	0 seconds											
or more informatio	n regarding material con	position	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	oHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl nthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted							
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	stislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Coupling Gel	0.4	mg	Supplier	Dimethyl Cyclosiloxanes	69430-24-6		0.04	mg
			Supplier	Trimethoxy(methyl)silane (C4H12O3Si)	1185-55-3		0.36	mg
Die	5.13	mg	Supplier	Silicon (Si)	7440-21-3		5.13	mg
Die Attach	0.3	mg	Supplier	Silver (Ag)	7440-22-4		0.225	mg
			Supplier	Phenolic Resin-2	54208-63-8		0.075	mg
Lead Frame	101.703	mg	Supplier	Silver (Ag)	7440-22-4		0.407	mg
			Supplier	Zinc (Zn)	7440-66-6		0.203	mg
			Supplier	Iron (Fe)	7439-89-6		2.64	mg
			Supplier	Copper (Cu)	7440-50-8		98.3	mg
			Supplier	Phosphorus (P)	7723-14-0		0.153	mg
Mold Compound-White	327.22	mg	Supplier	Titanium Dioxide (TiO2)	13463-67-7		81.805	mg
			В	Brominated Bisphenol A Diglycidyl Ether	40039-93-8		9.8166	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		44.1747	mg
			В	Antimony Trioxide (Sb2O3)	1309-64-4		9.8166	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		163.61	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		17.9971	mg
Plating	28.5	mg	Supplier	Tin (Sn)	7440-31-5		28.5	mg
Wire Bond - Au	1.65	mg	Supplier	Gold (Au)	7440-57-5		1.65	mg