



**PRODUCT DISCONTINUANCE NOTIFICATION**  
**EOL-000319**  
**Date: 3JUN2021**

P1/3

Semtech Corporation, 200 Flynn Road, Camarillo CA 93012

**Product Discontinuance Details**

**Purpose, Description and Effect of Change:**

This notification is to inform your company that Semtech is discontinuing the manufacture of the product listed below. In accordance with Semtech's product discontinuation policy, we are hereby giving notice of these product changes in order for your company to make any final lifetime purchases of the discontinued product that are still in supply.

**Part Number(s) Affected:**

RCLAMP0531Z.TFT/RCLAMP0531Z.TNT

**Customer Part Number(s) Affected:**  N/A

**Replacement or Alternate Part Number(s)**

N/A or Not Offered

RCLAMP5031ZATFT

**Last Time Buy (LTB) Date**

1DEC2021

**Must Accept Final Delivery by**

1JUN2022

**Sample Availability of Alt. Part**

N/A

**Qualification Report Availability of Alt. Part**

N/A

**Supporting Documents for Alternate or Replacement parts/Attachments:**

- RCLAMP5031ZA Datasheet attached
- Qualification report available upon request

**Last Time Buy Conditions**

We request you carefully review this information and notify your purchasing offices and buyers to place your company's final purchases for available discontinued products as soon as possible according to the following last time buy terms and conditions.

- 1. Availability:** The *Last Time Buy Date* and *Date to Accept Final Delivery* are noted above. All orders must have a *requested ship date before the Date to Accept Final Delivery* or the order will be rejected. *The Last Time Buy Date automatically expires when the final available inventory quantity has been scheduled and sold.*
- 2. Pricing:** The product unit price will be subject to Semtech's individual price quotation of your company's last time buy requirements.
- 3. Order Acceptance/Change Conditions:**
  - A. Semtech will accept last time orders from your company for the discontinued products as "Firm and Final". As such, these orders will not be subject to any reschedule, cancellation, or termination by your company without Semtech's prior written authorization and payment of full termination charges.
  - B. Semtech reserves its right to make changes in the scheduled delivery dates, or to terminate remaining undelivered quantities of your company's last time buy order, due to changes in Semtech's last time manufacturing capabilities, or for commercially impracticable circumstances, which makes delivery not feasible.



**PRODUCT DISCONTINUANCE NOTIFICATION**  
**EOL-000319**  
**Date: 3JUN2021**

P2/3

4. **Quantities:** The following applies to final buy quantities for the available discontinued product:
- A. **First:** The quantities in any existing unfilled orders and contracts acknowledged by Semtech will be honored, then
  - B. **Next:** The unfilled quantities in any volume agreement(s) or quantities in unexpired standalone quote(s) will be accepted, and
  - C. **Finally:** Any additional reasonable quantity of product that Semtech quotes based upon your company's identified requirements will be taken.

IN THE EVENT OF CONFLICT FOR THE LIMITED AVAILABILITY PRODUCT, QUANTITIES FOR CUSTOMER'S OR DISTRIBUTOR'S ORDERS WILL BE DETERMINED ON A FIRST-COME FIRST-SERVE BASIS; AND WILL BE SUBJECT TO SEMTECH'S AVAILABLE INVENTORY AND REMAINING MANUFACTURING CAPACITY FOR THE PRODUCT.

**Limited Warranty**

All discontinued product orders subject to this notice shall carry Semtech's standard limited warranty; or, if applicable, the warranty set forth in a duly executed formal contract between Semtech and your company will apply; except that:

- 1. Semtech will accept all valid warranty claims for credit only, unless a replacement order is otherwise agreed upon by Semtech and the replacement parts can be manufactured or delivered from remaining inventory.
- 2. The applicable warranty period for making any return claims for discontinued products will be no later than ninety (90) days following delivery of the discontinued products.
- 3. Any return claims must be made under Semtech's current Return Material Authorization "RMA" procedures.

**Additional Provisions**

SEMTECH ACCEPTS NO LIABILITY FOR EXCESS REPROCUREMENT COSTS OR FOR ANY SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES WHATSOEVER ASSOCIATED WITH THIS NOTICE, WITH ITS PRODUCTS, OR WITH THE FINAL MANUFACTURE AND PERFORMANCE AGAINST ANY LAST TIME BUY ORDERS RELATED TO THE DISCONTINUED PRODUCTS COVERED BY THIS NOTICE.




We regret the inconvenience and impact this notice may cause your company. Semtech's sales, marketing, and distribution personnel stand ready to assist you in placing your company's final orders, or in providing the product information you require.

For product inquiries or purchase order information, please contact your local Semtech sales representative.



**PRODUCT DISCONTINUANCE NOTIFICATION**  
**EOL-000319**  
**Date: 3JUN2021**

P3/3

Issuing Authority			
<b>Semtech Business Unit:</b>	PROTECTION		
<b>Semtech Contact Info:</b>	<table border="1"><tr><td>Les Fang Yuen  Semtech Corporation Qualit Assurance 200 Flynn Road Camarillo, CA 93012 lfangyuen@semtech.com Office: (949) 269-4443 Fax: (805) 498-3804</td><td></td></tr></table>	Les Fang Yuen  Semtech Corporation Qualit Assurance 200 Flynn Road Camarillo, CA 93012 lfangyuen@semtech.com Office: (949) 269-4443 Fax: (805) 498-3804	
Les Fang Yuen  Semtech Corporation Qualit Assurance 200 Flynn Road Camarillo, CA 93012 lfangyuen@semtech.com Office: (949) 269-4443 Fax: (805) 498-3804			
FOR FURTHER INFORMATION & WORLDWIDE SALES COVERAGE: <a href="http://www.semtech.com/contact/index.html#support">http://www.semtech.com/contact/index.html#support</a>			

## PROTECTION PRODUCTS


### Description

RClamp® TVS diodes are designed to protect sensitive electronics from damage or latch-up due to ESD. This device offers desirable characteristics for board level protection including fast response time, low operating and clamping voltage, and no device degradation.

RClamp®5031ZA features extremely good ESD protection characteristics highlighted by low typical dynamic resistance of 0.17 Ohms, low peak ESD clamping voltage, and high ESD withstand voltage (+/-17kV contact per IEC 61000-4-2). Low maximum capacitance (0.45pF at  $V_R=0V$ ) minimizes loading on sensitive circuits. Each device will protect one high-speed data line operating at 5 Volts.

RClamp5031ZA is in a DFN 0.60x0.30x0.25 mm 2-Lead package. The small package gives the designer the flexibility to protect single lines in applications where arrays are not practical. The combination of small size and high ESD surge capability makes them ideal for use in portable applications.

### Package Dimension (mm)



### Features

- High ESD withstand Voltage: +/-17kV (Contact) per IEC 61000-4-2 and +/- 24kV (Air) per IEC 61000-4-2
- Ultra-small package
- Protects one data line
- Low ESD clamping voltage
- Working voltage: 5V
- Low capacitance: 0.45pF maximum
- Low leakage current
- Low dynamic resistance: 0.17Ω (typ.)
- Solid-state silicon-avalanche technology


### Mechanical Characteristics

- Package: DFN 0.60x0.30x0.25 mm 2-Lead
- Pb-free, Halogen Free, RoHS/WEEE compliant
- Lead Finish: Pb-free,
- Marking: Marking code
- Packaging: Tape and Reel

### Applications

- USB 3.0/ USB 3.1 Gen 1
- USB Type-C
- MiPi/MDDI
- MHL
- FM antenna
- Wearables

### Schematic & Pin Configuration



## Absolute Maximum Rating

Rating	Symbol	Value	Units
Peak Pulse Current (tp = 1.2/50μs)	I <sub>PP</sub>	4	A
ESD per IEC 61000-4-2 (Air) <sup>(2)</sup> ESD per IEC 61000-4-2 (Contact) <sup>(2)</sup>	V <sub>ESD</sub>	±24 ±17	kV
Operating Temperature	T <sub>OP</sub>	-40 to +85	°C
Junction Temperature and Storage Temperature	T <sub>J</sub> and T <sub>STG</sub>	-55 to +150	°C

## Electrical Characteristics (T=25°C unless otherwise specified)


Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Reverse Stand-Off Voltage	V <sub>RWM</sub>				5	V
Reverse Breakdown Voltage	V <sub>BR</sub>	I <sub>t</sub> = 10mA	6.5	8.5	10.5	V
Holding Current	I <sub>H</sub>	V = V <sub>H</sub>		100		mA
Reverse Leakage Current	I <sub>R</sub>	V <sub>RWM</sub> = 5V		<5	50	nA
Clamping Voltage	V <sub>C</sub>	tp = 8/20μs I <sub>PP</sub> = 4A			13	V
ESD Clamping Voltage <sup>2</sup>	V <sub>C</sub>	tp = 0.2/100ns I <sub>PP</sub> = 4A		5		V
				7		
Dynamic Resistance <sup>2,3</sup>	R <sub>DYN</sub>	tp = 0.2/100ns		0.17		Ω
Junction Capacitance	C <sub>J</sub>	V <sub>R</sub> = 0V, f = 1MHz T = 25°C		0.35	0.45	pF

Notes:


- ESD gun return path connected to ESD ground plane.
- Transmission Line Pulse Test (TLP) Settings: tp = 100ns, tr = 0.2ns, I<sub>TLP</sub> and V<sub>TLP</sub> averaging window: t1 = 70ns to t2 = 90ns.
- Dynamic resistance calculated from I<sub>TLP</sub> = 4A to I<sub>TLP</sub> = 16A

# Typical Characteristics


**ESD Clamping (8kV Contact per IEC 61000-4-2)**




**ESD Clamping (-8kV Contact per IEC 61000-4-2)**




**TLP Characteristic (Positive Pulse)**




**Clamping Voltage Waveform (tp=1.2/50 $\mu\text{s}$ )**



**Capacitance vs. Reverse Voltage**




**Insertion Loss - S21**




# Typical Characteristics (Continued)


5Gb/s (USB 3.0) Eye Diagram with RClamp5031ZA




5Gb/s (USB 3.0) Eye Diagram without RClamp5031ZA



10Gb/s (USB 3.1) Eye Diagram with RClamp5031ZA



10Gb/s (USB 3.1) Eye Diagram without RClamp5031ZA



# Application Information

## Assembly Guidelines

The figure at the right details Semtech’s recommended mounting pattern. Recommended assembly guidelines are shown in Table 1. Note that these are only recommendations and should serve only as a starting point for design since there are many factors that affect the assembly process. Exact manufacturing parameters will require some experimentation to get the desired solder application.

## Solder Stencil

Stencil design is one of the key factors which will determine the volume of solder paste which is deposited onto the land pad. The area ratio of the stencil aperture will determine how well the stencil will print. The area ratio takes into account the aperture shape, aperture size, and stencil thickness. A minimum area ratio of 0.66 is preferred for the subject package. The area ratio of a rectangular aperture is given as:

$$\text{Area Ratio} = (L * W) / (2 * (L + W) * T)$$

Where:


L = Aperture Length

W = Aperture Width

T = Stencil Thickness

Semtech recommends a stencil with square aperture and rounded corners for consistent solder release. The stencil should be laser cut with electro-polished finish. A stencil thickness of 0.075mm (0.003”) is recommended. A 0.100mm (0.004”) stencil may be used, however the stencil opening may need to be increased slightly to achieve the desired area ratio to ensure proper solder coverage on the pad.

## Recommended Mounting Pattern



All Dimensions are in mm.


 Land Pad.  Stencil opening  Component

Table 1 - Assembly Guidelines

Assembly Parameter	Recommendation
Solder Stencil Design	Laser Cut, Electro-Polished
Aperture Shape	Rectangular with Rounded Corners
Solder Stencil Thickness	0.075mm (0.003”) or 0.100mm (0.004”)
Solder Paste Type	Type 4 Size Sphere or Smaller
Solder Reflow Profile	Per JEDEC J-STD-020
PCB Solder Pad Design	Solder Mask Defined or Non Solder Mask Defined
PCB Pad Finish	OSP or NiAu




## Outline Drawing - DFN 0.60x0.30x0.25 mm 2-Lead



- NOTES:
1. CONTROLLING DIMENSIONS ARE IN MILLIMETERS (ANGLES IN DEGREES).

## Land Pattern - DFN 0.60x0.30x0.25 mm 2-Lead




- NOTES:
1. CONTROLLING DIMENSIONS ARE IN MILLIMETERS (ANGLES IN DEGREES).
  2. THIS LAND PATTERN IS FOR REFERENCE PURPOSES ONLY. CONSULT YOUR MANUFACTURING GROUP TO ENSURE YOUR COMPANY'S MANUFACTURING GUIDELINES ARE MET.

## Marking Code

r

## Tape and Reel Specification



## Ordering Information

Part Number	Qty per Reel	Reel Size
RClamp5031ZATFT	15,000	7"



---

## Important Notice

Information relating to this product and the application or design described herein is believed to be reliable, however such information is provided as a guide only and Semtech assumes no liability for any errors in this document, or for the application or design described herein. Semtech reserves the right to make changes to the product or this document at any time without notice. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. Semtech warrants performance of its products to the specifications applicable at the time of sale, and all sales are made in accordance with Semtech's standard terms and conditions of sale.

SEMTECH PRODUCTS ARE NOT DESIGNED, INTENDED, AUTHORIZED OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT APPLICATIONS, DEVICES OR SYSTEMS, OR IN NUCLEAR APPLICATIONS IN WHICH THE FAILURE COULD BE REASONABLY EXPECTED TO RESULT IN PERSONAL INJURY, LOSS OF LIFE OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. INCLUSION OF SEMTECH PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE UNDERTAKEN SOLELY AT THE CUSTOMER'S OWN RISK. Should a customer purchase or use Semtech products for any such unauthorized application, the customer shall indemnify and hold Semtech and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs damages and attorney fees which could arise.

The Semtech name and logo are registered trademarks of the Semtech Corporation. All other trademarks and trade names mentioned may be marks and names of Semtech or their respective companies. Semtech reserves the right to make changes to, or discontinue any products described in this document without further notice. Semtech makes no warranty, representation or guarantee, express or implied, regarding the suitability of its products for any particular purpose. All rights reserved.

© Semtech 2020

---

## Contact Information

Semtech Corporation  
200 Flynn Road, Camarillo, CA 93012  
Phone: (805) 498-2111, Fax: (805) 498-3804  
[www.semtech.com](http://www.semtech.com)