PCN Number:	20171016000	PCN Date:		)3, 2017	
Title: Datasheet for INA1650-Q1					
Customer Contact:	PCN Manager		Dept:	Quality Services	
Change Type:			· _		
Assembly Site		Design	Wafei	r Bump Site	
Assembly Process	$\square$	Data Sheet	Wafei	r Bump Material	
Assembly Material	S	Part number change	Wafei	r Bump Process	
Mechanical Specifi	ication	Test Site	Wafei	r Fab Site	
Packing/Shipping/	Labeling	Test Process		r Fab Materials	
			Wafei	r Fab Process	
Notification Details					
<b>Description of Chang</b>	je:				
The product datasheet The following change h	(s) is being upda	ouncing an information out the summarized belo urther details.			
INSTRUMENTS		e		INA1650-Q1 2017-REVISED OCTOBER 2017	
Changes from Original (Au		1. H. MANAR		Page	
<ul> <li>Recommended supply ra text, graphs, and circuit of</li> </ul>	ange of the INA1650-Q diagrams, was remove	1 was reduced from 36 V to 24 V d or modified to reflect the 24 V		o 36 V operation in	
Recommended supply rates text, graphs, and circuit of The datasheet number	ange of the INA1650-Q diagrams, was remove	1 was reduced from 36 V to 24 V d or modified to reflect the 24 V	maximum supply.	o 36 V operation in 1	
Recommended supply ra text, graphs, and circuit of The datasheet number Device Family	ange of the INA1650-Q diagrams, was remove	1 was reduced from 36 V to 24 V d or modified to reflect the 24 V Change From:	maximum supply.	e To:	
Recommended supply rates, graphs, and circuit of text, graphs,	ange of the INA1650-Q diagrams, was removed will be changing	1 was reduced from 36 V to 24 V d or modified to reflect the 24 V Change From: SBOS772	Chang SBOS	e To:	
Recommended supply ratext, graphs, and circuit of text, graphs,	ange of the INA1650-Q diagrams, was removed will be changing e reviewed at the	1 was reduced from 36 V to 24 V d or modified to reflect the 24 V Change From: SBOS772 datasheet links provided	Chang SBOS	e To:	
Recommended supply rates, graphs, and circuit of text, graphs,	ange of the INA1650-Q diagrams, was removed will be changing e reviewed at the	1 was reduced from 36 V to 24 V d or modified to reflect the 24 V Change From: SBOS772 datasheet links provided	Chang SBOS	e To:	
Recommended supply ratext, graphs, and circuit of text, graphs,	ange of the INA1650-Q diagrams, was removed will be changing e reviewed at the	1 was reduced from 36 V to 24 V d or modified to reflect the 24 V Change From: SBOS772 datasheet links provided	Chang SBOS	e To:	
Recommended supply ratext, graphs, and circuit of text, graphs, and text, g	ange of the INA1650-Q diagrams, was removed will be changing e reviewed at the oduct/INA1650-Q	1 was reduced from 36 V to 24 V d or modified to reflect the 24 V Change From: SBOS772 datasheet links provided	Chang SBOS7	e To: 772A	
Recommended supply ratext, graphs, and circuit of text, graphs, and text, g	ange of the INA1650-Q diagrams, was removed will be changing e reviewed at the duct/INA1650-Q in descriptions ar	1 was reduced from 36 V to 24 V d or modified to reflect the 24 V Change From: SBOS772 datasheet links provided 1	Chang Chang SBOS7 d. n the figure a	e To: 772A	
<ul> <li>Recommended supply ratext, graphs, and circuit of text, graphs, and text, graphs,</li></ul>	ange of the INA1650-Q diagrams, was removed will be changing e reviewed at the duct/INA1650-Q in descriptions ar	1 was reduced from 36 V to 24 V d or modified to reflect the 24 V Change From: SBOS772 datasheet links provided 1 od the interconnections i	Chang Chang SBOS7 d. n the figure a i <b>ability (pos</b>	e To: 772A accurately.	
<ul> <li>Recommended supply ratext, graphs, and circuit of text, graphs, and circuit of Device Family</li> <li>INA1650-Q1</li> <li>These changes may be http://www.ti.com/pro</li> <li>Reason for Change:</li> <li>To reflect the device piece for the device piece for the device piece for the device piece for the actual device.</li> </ul>	ange of the INA1650-Q diagrams, was removed will be changing e reviewed at the duct/INA1650-Q in descriptions ar on Fit, Form, Fu This is a specific	1 was reduced from 36 V to 24 V d or modified to reflect the 24 V Change From: SBOS772 datasheet links provided 1 of the interconnections inction, Quality or Reli	n the figure a <b>iability (pos</b>	e To: 772A accurately.	
<ul> <li>Recommended supply ratext, graphs, and circuit of text, graphs, and circuit of Device Family</li> <li>INA1650-Q1</li> <li>These changes may be http://www.ti.com/pro</li> <li>Reason for Change:</li> <li>To reflect the device piece for the device piece for the device piece for the device piece for the actual device.</li> </ul>	ange of the INA1650-Q diagrams, was removed will be changing e reviewed at the duct/INA1650-Q in descriptions ar on Fit, Form, Fu This is a specific	1 was reduced from 36 V to 24 V         d or modified to reflect the 24 V         .         Change From:         SBOS772         datasheet links provided         1         add the interconnections in         nction, Quality or Relistion change announcer	n the figure a <b>iability (pos</b>	e To: 772A accurately.	
<ul> <li>Recommended supply ratext, graphs, and circuit of text, graphs, and circuit of Device Family</li> <li>INA1650-Q1</li> <li>These changes may be http://www.ti.com/proprogrammed for Change:</li> <li>To reflect the device pier Anticipated impact of No anticipated impact. to the actual device.</li> <li>Changes to product</li> <li>None.</li> </ul>	ange of the INA1650-Q diagrams, was removed will be changing e reviewed at the duct/INA1650-Q in descriptions ar on Fit, Form, Fu This is a specific	1 was reduced from 36 V to 24 V         d or modified to reflect the 24 V         .         Change From:         SBOS772         datasheet links provided         1         add the interconnections in         nction, Quality or Relistion change announcer	n the figure a <b>iability (pos</b>	e To: 772A accurately.	
<ul> <li>Recommended supply ratext, graphs, and circuit of text, to the actual device.</li> </ul>	ange of the INA1650-Q diagrams, was removed will be changing e reviewed at the duct/INA1650-Q in descriptions ar on Fit, Form, Fu This is a specific	1 was reduced from 36 V to 24 V         d or modified to reflect the 24 V         .         Change From:         SBOS772         datasheet links provided         1         add the interconnections in         nction, Quality or Relistion change announcer	n the figure a <b>iability (pos</b>	e To: 772A accurately.	

For questions regarding this notice, e-mails can be sent to the regional contacts shown below or your local Field Sales Representative.

Location	E-Mail
USA	PCNAmericasContact@list.ti.com
Europe	PCNEuropeContact@list.ti.com
Asia Pacific	PCNAsiaContact@list.ti.com
Japan	PCNJapanContact@list.ti.com