ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES® International and Pan-Ame	annockburn, Illinois.	All rights reserved u	under both	This docume level parts, th	ent is a declaration en	n of the sub compasses a	stances w all lower l	ithin the manufactur evel materials for w	er listed iter hich the mar	n. Note: if ufacturer	the item is an as has engineering	sembly with low responsibility.
	1.1IPC Web Site for Information on IPC-1752 Standard http://www.ipc.org/IPC-175xForm Typ Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Information					on		
upplier Information												
mpany name* Company unique ID				Unique ID Authority				Response Date*				
semi									2023-06-08			
ontact Name	Title - Contact]	Phone - Contact*				Email - Contact*			
uct-Env-Stewards Product Enviro Compliance					NA				Product-Env-Stewards@onsemi.com			
athorized Representative* Title - Representative				1	Phone - Representative*				Email - Representative*			
Product-Env-Stewards Product Enviro Compl			Compliance		NA			Product-Env-Stewards@onsemi.com				
Requester Item Number N	Ifr Item Number	Mfr Item Name			Effective Date	Version	Ma	Manufacturing Site		eight*	UOM	Unit Type
F	AN53526UC00X	N53526UC00X DC/DC DVS Buck			2023-06-08		PB	РВВ		33069	mg	Each
Ianufacturing Proccess Information		·			-							
Terminal Plating / Grid Array Material	Terminal Base Alloy J-ST		J-STD-020 MSL	Rating	Peak Process Body Temper		nperature	ture Max Time at Peak Temp		e Numbe	r of Reflow Cyc	les
SnAgCu CU Alloy			1		260	(2	30	seconds	3		
omments												
vel 1 - maximum time at peak temperature du	ring soldering is 10-	30 seconds										
or more information regarding material comp	osition please refer	o page 3										

RoHS Material Composition Declaration				Declaration Type *	Detailed					
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Disobutyl phthalate (DIBP).									
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of					
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted					
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all					
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the					
Supplier Digital Signature Ra	stislav Drska	Le								

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Backside Protection Film	0.103505	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.0217	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0019	mg
			Supplier	Silica (SiO2)	14464-46-1		0.0583	mg
			Supplier	2,4,6-Tris[Bis(Methoxymethyl)Amino]- 1,3,5-Triazine	3089-11-0		0.0217	mg
Die	2.31625	mg	Supplier	Silicon (Si)	7440-21-3		2.2956	mg
			Supplier	Aluminum (Al)	7429-90-5		0.0206	mg
Solder Ball	0.912574	mg	Supplier	Silver (Ag)	7440-22-4		0.0515	mg
			Supplier	Tin (Sn)	7440-31-5		0.8555	mg
			Supplier	Copper (Cu)	7440-50-8		0.0055	mg
Under Bump Metal	7.4E-4	mg	Supplier	Titanium (Ti)	7440-32-6		0	mg
			Supplier	Copper (Cu)	7440-50-8		0.0007	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).