ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES® International and Pa	IPC. Bannockł	ourn. Illinois. A	Il rights reserved untions.	under both	This docume level parts, t	ent is a declaration entities the declaration entities and the declaration entities and the declaration entities and the declaration entities are an entities and the declaration entities are an entities and the declaration entities are an entites are an	on of the su	bstances w all lower	vithin the manufactu level materials for w	rer listed it which the m	em. Note: if anufacturer	the item is an as has engineering	sembly with low responsibility.	
			Form Type Distribute	e * Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials					ials and M	s and Mfg Information				
upplier Information														
Company name* Con			Company unique ID			Unique ID Authority				Respons	Response Date*			
nsemi										2023-06-08				
ontact Name	tact Name Title - Contact					Phone - Contact*				Email - Contact*				
Product-Env-Stewards Product Enviro Co			o Compliance		NA				Product-Env-Stewards@onsemi.com					
Authorized Representative* Title - Representative			entative		Phone - Representative*			Email - Representative*						
Product-Env-Stewards Pro			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Requester Item Number	Mfr Item	n Number	Mfr Item Name			Effective Date	Version	М	lanufacturing Site	7	Weight*	UOM	Unit Type	
	FAN535	CAN53541UCX DC/DC Buck 5.0A		A		2023-06-08		PI	РВВ		1.468594	mg	Each	
Ianufacturing Proccess Informa	ntion							<u>_</u>		·				
Terminal Plating / Grid Array M	d Array Material Terminal Base Alloy J-			J-STD-020 MSI	L Rating	Peak Process Body Temperature Max Time at Peal				Temperature Number of Reflow Cycles				
SnAgCu CU Alloy			1		260		С	30	secon	ds 3				
omments														
vel 1 - maximum time at peak temperat	ure during so	ldering is 10-3	0 seconds											
or more information regarding material	l composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed					
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Disobutyl phthalate (DIBP).									
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of					
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted					
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the					
Supplier Digital Signature Ra	stislav Drska	Le								

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).										
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure		
Die	3.25064	mg	Supplier	Silicon (Si)	7440-21-3		3.2281	mg		
			Supplier	Aluminum (Al)	7429-90-5		0.0225	mg		
Solder Ball	1.21677	mg	Supplier	Silver (Ag)	7440-22-4		0.0487	mg		
			Supplier	Tin (Sn)	7440-31-5		1.162	mg		
			Supplier	Copper (Cu)	7440-50-8		0.0061	mg		
Under Bump Metal	Jnder Bump Metal 0.001184	U	Supplier	Titanium (Ti)	7440-32-6		0.0003	mg		
			Supplier	Copper (Cu)	7440-50-8		0.0009	mg		

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signar range of distribution unless otherwise noted)