ASSOCIATION CONNECTING ELECTROMICS INDUSTRIES®	PC. Bannockh	ourn, Illinois, A	Il rights reserved untions.	under both	This docume level parts, t	ent is a declaration entities the declaration entities and the declaration entities and the declaration entities and the declaration entities are an	on of the su compasses	bstances v all lower	vithin the manufactu level materials for v	rer listed i which the r	tem. Note:	if the item is an as r has engineering	sembly with low responsibility.	
				Form Type Distribute	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi				ials and M	als and Mfg Information				
upplier Information														
Company name* Com			Company unique ID			Unique ID Authority				Respon	Response Date*			
nsemi										2023-06-08				
Contact Name	t Name Title - Contact					Phone - Contact*				Email - Contact*				
Product-Env-Stewards Product Enviro Co			o Compliance			NA				Product-Env-Stewards@onsemi.com				
Authorized Representative* Title - Representative			sentative	ntative I		Phone - Representative*			Email - Representative*					
Product-Env-Stewards Produ			Product Enviro Compliance			NA				Produc	Product-Env-Stewards@onsemi.com			
Requester Item Number	Mfr Item	Number	Mfr Item Name			Effective Date	Date Version Manufacturing Site		lanufacturing Site		Weight*	UOM	Unit Type	
	FAN486	FAN48630UC315X 3MHZ DC/DC Boo		oost 1.5A	2023-06-08			PI	РВВ		3.38704	mg	Each	
Ianufacturing Proccess Information	ion											· · ·		
Terminal Plating / Grid Array Ma	erial Terminal Base Alloy J-			J-STD-020 MSI	L Rating	Peak Process Body Temperature Max T			e Max Time at Peak	. Tempera	ure Num	ber of Reflow Cyc	les	
SnAgCu CU Alloy			1		260		С	30	secor	ids 3				
omments														
vel 1 - maximum time at peak temperatu	re during sol	dering is 10-3	0 seconds											
or more information regarding material	composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Disobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.											
Supplier Digital Signature Ra	stislav Drska	Le									

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).										
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure		
Die 2.40	2.40717	mg	Supplier	Silicon (Si)	7440-21-3		2.3978	mg		
			Supplier	Aluminum (Al)	7429-90-5		0.0094	mg		
Solder Ball	0.973411	mg	Supplier	Silver (Ag)	7440-22-4		0.0389	mg		
			Supplier	Tin (Sn)	7440-31-5		0.9296	mg		
			Supplier	Copper (Cu)	7440-50-8		0.0049	mg		
Under Bump Metal 0.	0.006459	mg	Supplier	Titanium (Ti)	7440-32-6		0.0052	mg		
			Supplier	Copper (Cu)	7440-50-8		0.0012	mg		

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signar range of distribution unless otherwise noted)