IPC ASSOCIATION CONNECT ELECTRONICS INDUSTR	Material Compo © Copyright 2005. IP international and Pan-	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.								
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				e *	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					fg Informat	ion	
upplier Infor									,					
Company name*			Company unique ID			J	Unique ID Authority				Response Date*			
onsemi										2023-06-08				
Contact Name		Title - Contact			I	Phone - Contact*				Email - Contact*				
Product-Env-Stev	vards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
authorized Repres	sentative*	Title - Representative			I	Phone - Representative*				Email - Representative*				
Product-Env-Stev	vards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Reques	Requester Item Number Mfr Item		m Number Mfr Item Name				Effective Date	Pective Date Version Manufacturing S		Manufacturing Site	,	Weight*	UOM	Unit Type
		NCV7428MW3R2G LIN + 3,3V 70N		LIN + 3,3V 70MA	LDO	2023-0			PHG		2	23.83	mg	Each
Ianufacturing	g Proccess Informati	ion						·					·	
Terminal Plating / Grid Array Material To			Ferminal Base Alloy J-STD-020 MSI		SL Rating	Peak Process Body Temperature		re Max Time at Peak	Temperat	ure Numb	per of Reflow Cyc	eles		
Matte Tin (Sn) - annealed		CU Alloy 1			260 C		30	secon	ds 3					
omments														
vel 1 - maximum	time at peak temperatur	e during sol	dering is 10-3	30 seconds										
or more informat	tion regarding material c	omposition	please refer to	page 3										

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	1.43	mg	Supplier	Silicon (Si)	7440-21-3		1.43	mg
Die Attach	0.24	mg	Supplier	Isobornyl Methacrylate	7534-94-3		0.0144	mg
			Supplier	Silver (Ag)	7440-22-4		0.1956	mg
			Supplier	Isobornyl Acrylate	5888-33-5		0.0144	mg
			Supplier	Misc.	Proprietary Data		0.0012	mg
			Supplier	Tricyclo[5.2.1.02,6]decanedimethanol Diacrylate (C18H24O4)	42594-17-2		0.0144	mg
Lead Frame	9.25	mg	Supplier	Tin (Sn)	7440-31-5		0.0231	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0203	mg
			Supplier	Chromium (Cr)	7440-47-3		0.0231	mg
			Supplier	Copper (Cu)	7440-50-8		9.1834	mg
Lead Frame plating	0.19	mg	Supplier	Silver (Ag)	7440-22-4		0.19	mg
Mold Compound-Black	11.62	mg	Supplier	Silica Amorphous (SiO2)	7631-86-9		0.9296	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0581	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		0.2324	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		9.1217	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		0.9296	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.3486	mg
Plating	0.75	mg	Supplier	Tin (Sn)	7440-31-5		0.75	mg
Wire Bond - Au	0.35	mg	Supplier	Gold (Au)	7440-57-5		0.35	mg