

LINEAR TECHNOLOGY MATERIALS DECLARATION

ltc2246cuh#trpbf

(Engineering Calculation)

QFN 5mm X 5mm Exp. Pad

(printed on: 2020-07-11 21:50:00)

TOTAL MASS (g) : 0.065175

| COMPONENT MATERIAL | VENDOR/ INDUSTRY NAMES | CONSTITUENT NAME | CAS NUMBER | CONSTITUENT MASS (g) | CONSTITUENT (PPM) OF MATERIAL | CONSTITUENT (PPM) OF TOTAL PKG. | | |
|--------------------------------|----------------------------------|--------------------------------|------------|----------------------|-------------------------------|---------------------------------|----------------|----------------------|
| Active Device | Linear Technology | Silicon (Si) | 7440-21-3 | 0.002502 | 1000000 | 38388.7929688 | | |
| Die Coat | Dow Corning | Silicone | 69430-27-9 | 0.000000 | 0 | 0 | | |
| Lead Frame | Cu | Copper (Cu) | 7440-50-8 | 0.028382 | 975000 | 435471.90625 | | |
| | | Iron (Fe) | 7439-89-6 | 0.000699 | 24000 | 10724.9267578 | | |
| | | Phosphorus (P) | 7723-14-0 | 0.000009 | 300 | 138.089187622 | | |
| | | Zinc (Zn) | 7440-66-6 | 0.000020 | 700 | 306.864837646 | | |
| | | Nickel (Ni) | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Silicon (Si) | 7440-21-3 | 0.000000 | 0 | 0 | | |
| | | Magnesium (Mg) | 7439-95-4 | 0.000000 | 0 | 0 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| Lead Frame Total: | | | | 0.029110 | 1000000 | 446641.78125 | | |
| Plating | PMI | Exter. Plating Pb | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Exter. Plating Sn | 7440-31-5 | 0.001398 | 1000000 | 21454.0839844 | | |
| | | External Plating Total: | | | | 0.001398 | 1000000 | 21454.0839844 |
| | | Inter. Plating Ni | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Inter. Plating Ag | 7440-22-4 | 0.000635 | 1000000 | 9742.95898438 | | |
| Internal Plating Total: | | | | 0.000635 | 1000000 | 9742.95898438 | | |
| Die Attach | ELECTRICALLY CONDUCTIVE ADHESIVE | Silver (Ag) | 7440-22-4 | 0.001054 | 750000 | 16171.7773438 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| | | Lead (Pb) | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.000000 | 0 | 0 | | |
| | | Indium (In) | 7440-74-6 | 0.000000 | 0 | 0 | | |
| | | Metal Oxide | | 0.000000 | 0 | 0 | | |
| | | Antimony (Sb) | 7440-36-0 | 0.000000 | 0 | 0 | | |
| | | Resin (EP) | | 0.000351 | 250000 | 5385.47802734 | | |
| Die Attach Total: | | | | 0.001405 | 1000000 | 21557.2539062 | | |
| Encapsulation | MULTI-AROMATIC RESIN Br/Sb FREE | Resin (EP) | | 0.003888 | 130000 | 59654.5273438 | | |
| | | Bromine (Br) | 40039-93-8 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.025723 | 860000 | 394674.21875 | | |
| | | Antimony Trioxide (Sb2O3) | 1309-64-4 | 0.000000 | 0 | 0 | | |
| | | Metal Hydroxide | | 0.000000 | 0 | 0 | | |
| | | Carbon Black (C) | 1333-86-4 | 0.000299 | 10000 | 4587.62939453 | | |
| | | Encapsulation Total: | | | | 0.029910 | 1000000 | 458916.375 |
| Bond Wire Estimated | AFW/TANAKA/ Kn | Gold (Au) | 7440-57-5 | 0.000215 | 1000000 | 3298.796875 | | |
| | | | | | TOTAL MASS (g) : | 0.065175 | | |