ASSOCIATION CONNECTING ALLCTROMICS INDUSTRIES® International and Pan-	C. Bannockł	ourn. Illinois, A	ll rights reserved utions.	under both	This docume level parts, t	ent is a declaration entities the declaration entities and the declaration entities and the declaration entities and the declaration entities are an entities and the declaration entities are an entities and the declaration entities are an entite are an entities are an entities are an entite are	on of the su	bstances v all lower	within the manufactur level materials for w	rer listed it hich the m	em. Note: i anufacture	if the item is an as r has engineering	sembly with low responsibility.
			Form Type Distribute	 Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials 					ials and M	s and Mfg Information			
Supplier Information													
Company name*	Company uni	Company unique ID			Unique ID Authority				Response Date*				
nsemi									2023-06-08				
Contact Name	tet Name Title - Contact					Phone - Contact*				Email - Contact*			
Product-Env-Stewards Product Envir			riro Compliance			NA				Product-Env-Stewards@onsemi.com			
Authorized Representative* Title - Repre			esentative			Phone - Representative*				Email - Representative*			
Product-Env-Stewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Requester Item Number	Mfr Item Numb		Number Mfr Item Name			Effective Date Version Manufacturing Site		Ianufacturing Site		Weight*	UOM	Unit Type	
	MC78M	78M08ACDTRKG ANA 500MA 8V VI		VREG		2023-06-08	-08 MY		IY1	1	350.99	mg	Each
Aanufacturing Proccess Informati	on					·		·					
Terminal Plating / Grid Array Mat	rial Terminal Base Alloy J-S			J-STD-020 MS	L Rating	Peak Process Body Temperature Max Tim			e Max Time at Peak	Temperat	ure Numl	ber of Reflow Cyc	les
Matte Tin (Sn) - annealed CU Alloy		CU Alloy		1			260 C 30		seconds 3				
omments													
vel 1 - maximum time at peak temperatur	e during sol	Idering is 10-3) seconds										
or more information regarding material c	omposition	please refer to	page 3										

RoHS Material Composition Declaration				Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	(Pb), Mercury (Hg), Hexavalent Chro	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in ifies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of							
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted							
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).									
Exemption List Version	EL-2011/534/EU											
Declaration Signature												
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.												
Supplier Digital Signature	astislav Drska	Le										

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

	cable [E] enter the weigh			ance category (JIG or Requester) or enter a [F] Optionally enter the positive (+) and n				
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.2	mg	Supplier	Silicon (Si)	7440-21-3		0.2	mg
Die Attach	1.4	mg	А	Lead (Pb)	7439-92-1	7a	1.33	mg
			Supplier	Tin (Sn)	7440-31-5		0.07	mg
Lead Frame	214.64	mg	В	Nickel (Ni)	7440-02-0		0.4293	mg
			Supplier	Copper (Cu)	7440-50-8		214.2107	mg
Mold Compound-Black	129.65	mg		Phenolic Resin	proprietary data		10.372	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		10.372	mg
			Supplier	Carbon Black (C)	1333-86-4		0.6482	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		108.2577	mg
Plating	3.73	mg	Supplier	Tin (Sn)	7440-31-5		3.73	mg
Wire Bond - Cu	1.37	mg	Supplier	Copper (Cu)	7440-50-8		1.37	mg