	Material Composit © Copyright 2005. IPC,  international and Pan-An	Bannockb	urn, Illinois. A	ll rights reserved untions.	under both	This docum level parts, t	ent is a decla	ration of on encom	f the substances npasses all low	s within the manuf er level materials f	acturer listed or which the	d item. Note: i e manufacture	f the item is an a r has engineering	ssembly with lower responsibility.	
1752-21.1					Form Type Distribute	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					aterials and	ials and Mfg Information			
Supplier Inform	ation														
Company name*			Company unique ID			Unique ID Authority					Response Date*				
onsemi											2023-	2023-06-08			
Contact Name	Title - Contact				Phone - Contact*				Emai	Email - Contact*					
Product-Env-Stewards			Product Enviro Compliance				NA				Prod	Product-Env-Stewards@onsemi.com			
Authorized Representative*			Title - Representative			Phone - Representative*			Emai	Email - Representative*					
Product-Env-Stewa	Product Enviro Compliance				NA				Prod	Product-Env-Stewards@onsemi.com					
Requeste	Requester Item Number Mfr Item		n Number Mfr Item Name				Effective D	ate Ve	ersion	Manufacturing Sit	e	Weight*	UOM	Unit Type	
		NCV494BDR2G ANA		ANA SMPS DB END HI FREQ		1	2023-06-08			PH1		142.68	mg	Each	
Manufacturing	Proccess Information	1						·							
Terminal Plating / Grid Array Material Term			erminal Base A	inal Base Alloy J-STD-020 MSL Ra		L Rating	Peak Process Body Temperature Max		re Max Time at l	eak Tempe	ak Temperature Number of Reflow Cycles		cles		
Matte Tin (Sn) - annealed CU Alloy				1		260		С	30	sec	conds 3				
Comments															
level 1 - maximum ti	me at peak temperature d	luring sol	dering is 10-3	0 seconds											
For more information	on regarding material com	position p	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted						
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all						
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	stislav Drska	Le									

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

select a ROHS exemption, if appli sigma range of distribution unless	otherwise noted).	it of the substance of the Pl	PM concentration	[F] Optionally enter the positive (+) and n	legative (-) tolerance in per	cent (Note: percer	it tolerance values are	expected to cover a 3
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	2.73	mg	Supplier	Silicon (Si)	7440-21-3		2.73	mg
Die Attach	4.85	mg	Supplier	Silver (Ag)	7440-22-4		3.6375	mg
			Supplier	Epoxy resins	129915-35-1		1.2125	mg
Lead Frame	75.92	mg	Supplier	Silver (Ag)	7440-22-4		0.7592	mg
			Supplier	Zinc (Zn)	7440-66-6		0.1518	mg
			Supplier	Iron (Fe)	7439-89-6		1.9739	mg
			Supplier	Copper (Cu)	7440-50-8		73.035	mg
Mold Compound-Black	55.11	mg		Epoxy resin	proprietary data		2.7555	mg
			Supplier	Phenolic Resin	Proprietary Data		2.7555	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		1.1022	mg
			Supplier	Carbon Black (C)	1333-86-4		0.2756	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		48.2213	mg
Plating	3.73	mg	Supplier	Tin (Sn)	7440-31-5		3.73	mg
Wire Bond - Cu	0.34	mg	Supplier	Copper (Cu)	7440-50-8		0.34	mg