

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2005

© COPYRIGHT 2005

ALL RIGHTS RESERVED.

LOC
ALDIST
2

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	J6	REVISED PER ECR-18-010208	23JUL2018	BDA	SF

NOTES:

Bemerkungen:

	2-6µm Sn OVER Ni IN CRIMP-AREA 2-6µm Sn über Ni in der Crimpzone
	0.8µm Au OVER Ni IN CONTACT-AREA 0.8µm Au über Ni in der Kontaktzone
3	SUITABLE FOR Ø1.0-2.5mm Für Isolations Ø1.0-2.5mm geeignet
	0.8µm Au OVER 1.3µm Ni ON INSIDE OF WIRE BARREL AND CONTACT AREA 0.8µm Au über 1.3µm Ni in der Drahtcrimp und Kontaktzonen, sonst 1.3µm Ni

SUPERSEDED BY 350851-7	926895-7	926884-7	BRASS	
SUPERSEDED BY 350851-7	926895-6	926884-6	PHOS BRONZE	
	926895-3	926884-3	PHOS BRONZE	PRE-TIN
OBSOLETE	926895-2	926884-2	BRASS	
	926895-1	926884-1	BRASS	PRE-TIN
	LOOSE PIECE	PART NO.	MATERIAL	FINISH

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J. Skoda	07NOV2005	TE Connectivity	
DIMENSIONS: mm		CHK R. Vlcek	-		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD -	-	NAME UNIVERSAL MNL SOCKET 0.2-0.8 mm ² WIRE RANGE	
0 PLC	±0.2	PRODUCT SPEC	108-1031	SIZE	CAGE CODE
1 PLC	±0.2	APPLICATION SPEC	114-18011	A3	00779
2 PLC	±0.2	WEIGHT	-	DRAWING NO	C-926884
3 PLC	±	CUSTOMER DRAWING		SCALE	5:1
4 PLC	±			SHEET	1 OF 1
ANGLES	±1°			REV	J6
FINISH	SEE TABLE				

1470-19 (3/11)