ASSOCIATION ELECTRONICS	CONNECTING CONNECTING CONNECTING CONNECTING CONNECTING CONNECTING CONNECTING CONNECTING CONNECTING CONNECTING CONNECTING	PC, Bannockb	ourn, Illinois. A	All rights reserved untions.	nder both	This docume level parts, t	ent is a declarat he declaration	ion of th encompa	ne substances asses all lowe	within the er level mat	manufactur erials for wh	er listed it hich the m	em. Note: it anufacturer	f the item is an as has engineering	sembly with low responsibility.
752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					eous Materia	ials and Mfg Information				
upplier	Information														
Company name* Cor				Company unique ID			Unique ID Authority					Response Date*			
nsemi												2023-06-08			
ontact Na	ime	Title - Contact]	Phone - Contact*					Email - Contact*				
Product-E	nv-Stewards		Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com			
uthorized	Representative*	Title - Representative]	Phone - Representative*				Email - Representative*					
roduct-E	nv-Stewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
	Requester Item Number Mfr Item Num LM2576TV-A		n Number Mfr Item Name				Effective Date	ve Date Version Manufacturing Sit		ing Site	v	Veight*	UOM	Unit Type	
			TV-ADJG	G ANA ADJV .5A PWR SW REG			2023-06-08 MY1			1960.42		mg	Each		
Ianufac	turing Proccess Information	tion		1				_	ļ						
r	Terminal Plating / Grid Array Material		Terminal Base Alloy J-STD-020 M		J-STD-020 MS	L Rating	Peak Process Body Temperat		ure Max Time at Peak Tem		Temperatu	ire Numb	er of Reflow Cyc	les	
Matte Tin (Sn) - annealed		CU Alloy NA			0 C		30		second	ls 3					
omments															
or more ii	nformation regarding material	composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted						
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).								
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required Requester) and click on Submit Form to h			e drop-dowi	a. This will display the signature area. Digita	lly sign the declaration (if required by the						
Supplier Digital Signature	astislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	3.55	mg	Supplier	Silicon (Si)	7440-21-3		3.55	mg
Die Attach	82.83	mg	А	Lead (Pb)	7439-92-1	7a	78.6885	mg
			Supplier	Tin (Sn)	7440-31-5		4.1415	mg
Lead Frame	1297.64	mg	Supplier	Copper (Cu)	7440-50-8		1297.64	mg
Mold Compound-Black	543.9	mg		Phenolic Resin	proprietary data		32.634	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		54.39	mg
			Supplier	Carbon Black (C)	1333-86-4		2.7195	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		40.7925	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		413.364	mg
Plating	31.13	mg	Supplier	Tin (Sn)	7440-31-5		31.13	mg
Wire Bond - Cu	1.37	mg	Supplier	Copper (Cu)	7440-50-8		1.37	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted)