ASSOCIATION CONNECTING	Material Composit © Copyright 2005. IPC, international and Pan-An	Bannockb	urn, Illinois. A	ll rights reserved u ntions.	inder both This	s docume el parts, tl	ent is a decla he declaratio	ration of on encon	f the substance npasses all low	es within th ver level m	e manufactur aterials for wl	er listed ite hich the m	em. Note: anufacture	if the item is an as er has engineering	sembly with lower responsibility.
1752-21.1					Form Type * Distribute	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information				
Supplier Informa	ation														
Company name*			Company unique ID			Unique ID Authority					Response Date*				
onsemi												2023-06-08			
Contact Name			Title - Contact]	Phone - Contact*				Email - Contact*				
Product-Env-Stewards			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com					
Authorized Representative*			Title - Representative			Phone - Representative*				Email - Representative*					
Product-Env-Stewar	ds	Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com						
Requester	quester Item Number Mfr Item		Number Mfr Item Name			Effective D	ate Ve	ersion	Manufacturing Site		V	Veight*	UOM	Unit Type	
		NCV431BSNT1G Adjustable 1.24-10 20 mA S		6 V +/-1% Tolerand	ce, 0.05-	2023-06-08 MY1			1	4.08	mg	Each			
Manufacturing P	roccess Information	ı													
Terminal Plating / Grid Array Material Ter			erminal Base Alloy J-STD-020 MSL Rating		ting	Peak Process Body Temperature Max Tim		Гіте at Peak	eak Temperature Number of Reflow Cycles		les				
Matte Tin (Sn) - annealed CU Alloy 1				1		260		С	30		second	ls 3			
Comments															
level 1 - maximum tir	ne at peak temperature d	luring sol	dering is 10-3	0 seconds											
For more information	n regarding material com	position 1	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed								
Directive 2015/863/EU amending RoHS Directive 2011/65/EU													
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of								
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted								
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all								
Exemption List Version	EL-2011/534/EU												
Declaration Signature													
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the								
Supplier Digital Signature Ra	stislav Drska	Le											

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.42	mg	Supplier	Silicon (Si)	7440-21-3		0.42	mg
Die Attach	0.11	mg	Supplier	Epoxized Condensate Of Para- Hydrobenzaldehyde And Alkyl Phenol	129915-35-1		0.0352	mg
			Supplier	Aluminum Trioxide (Al2O3)	1344-28-1		0.0735	mg
			В	Antimony Pentoxide (Sb2O5)	1314-60-9		0.0013	mg
Lead Frame	5.78	mg	Supplier	Silver (Ag)	7440-22-4		0.0705	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0069	mg
			Supplier	Iron (Fe)	7439-89-6		0.1358	mg
			Supplier	Copper (Cu)	7440-50-8		5.565	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0017	mg
Mold Compound-Black	7.34	mg		Epoxy resin	proprietary data		0.367	mg
			Supplier	Phenolic Resin	Proprietary Data		0.367	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.1468	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0367	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		6.4225	mg
Plating	0.39	mg	Supplier	Tin (Sn)	7440-31-5		0.39	mg
Wire Bond - Au	0.04	mg	Supplier	Gold (Au)	7440-57-5		0.04	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).