IPC ASSOCIATION CO	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			der both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No. Homogeneous Materi					ials and Mfg Information				
upplier Iı	nformation								,						
Company name* Company unique II				ique ID	ue ID Unique ID A		Jnique ID Auth	E ID Authority Re			Response	Response Date*			
nsemi											2023-06-08				
Contact Nam	ne		Title - Contact			I	Phone - Contact*				Email - Contact*				
Product-Env	v-Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
uthorized R	Representative*	Title - Repre	Title - Representative			Phone - Representative*			Email - Representative*						
Product-Env-Stewards Prod				Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
R	Requester Item Number	Mfr Item	Number	mber Mfr Item Name			Effective Date Version Manufacturing Si		Anufacturing Site	W	eight*	UOM	Unit Type		
	FAN48618BUC53X 3MHZ DC/DC		3MHZ DC/DC Boo	ost 1.0A		2023-06-08 PBB		ВВ	1.	824028	mg	Each			
	uring Process Inform							·					·		
Te	erminal Plating / Grid Array N	Material T	erminal Base	Alloy J-S	STD-020 MSL	Rating	Peak Proc	ess Body T	emperatur	e Max Time at Peak	Temperatu	re Numb	er of Reflow Cyc	eles	
Sn	1AgCu	C	CU Alloy	1			260		C	30	second	s 3			
omments															
vel 1 - maxi	imum time at peak tempera	ture during sol	dering is 10-3	30 seconds											
or more info	ormation regarding materia	al composition	please refer t	o page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	led						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substa	ances per the definition above	Supplier Ac	ceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructional Complete all of the required	fields on all neggs of this form. Calcut th		a duan dawn. This will display the signature on	a Digitally sign	the declaration (if recurined by the						
Instructions: Complete all of the required Requester) and click on Submit Form to			e drop-down. This will display the signature ar	ea. Digitally sign	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Backside Protection Film	0.054758	mg		Epoxy resin	proprietary data		0.0115	mg
			Supplier	Carbon Black (C)	1333-86-4		0.001	mg
			Supplier	Acrylic resins	Proprietary Data		0.0115	mg
			Supplier	Silica (SiO2)	14464-46-1		0.0308	mg
Die	1.22114	mg	Supplier	Silicon (Si)	7440-21-3		1.2144	mg
			Supplier	Aluminum (Al)	7429-90-5		0.0067	mg
Solder Ball	0.547544	mg	Supplier	Silver (Ag)	7440-22-4		0.0219	mg
			Supplier	Tin (Sn)	7440-31-5		0.5229	mg
			Supplier	Copper (Cu)	7440-50-8		0.0027	mg
Under Bump Metal	5.86E-4	mg	Supplier	Titanium (Ti)	7440-32-6		0.0001	mg
			Supplier	Copper (Cu)	7440-50-8		0.0004	mg